

# A PLUS

## A606

1. Four wide circumferential tread grooves deliver the ride stability and offer excellent performance on wet conditions. Improved grooves and bead profile design offer better ride stability, endurance and handling performance.
2. Continuous tread blocks on both shoulder give great support to enhance the stability when cornering, the closed shoulders deliver excellent quiet ride.
3. Continuous solid center ribs and lateral tread blocks connected by rib-in-chain enhance steering stability, decrease block deformation and reduce energy loss.

SIZES DESCRIPTION	TREAD DEPTH		LOAD INDEX	SPEED SYMBOL	STD.RIM	SECTION WIDTH		OVERALL DIAMETER		LOAD CAPACITY		MAX. PER MISS
	mm	32nds				mm	inch	mm	inch	kg	lbs	
155/65R13	6.8	8.6	73	H	4.5	157	6.2	532	20.9	365	805	44
155/70R13	7.3	9.2	75	T	4.5	157	6.2	548	21.6	387	853	44
155/80R13	10.1	260	79	T	4.5	151	5.9	574	22.6	435	959	44
165/65R13	7.3	9.2	77	T	5	170	6.7	544	21.4	412	908	44
165/70R13	8.3	10.5	78	T	5	162	6.4	558	22.0	425	937	44
175/60R13	7.3	9.2	77	H	5	177	7	540	21.3	412	908	44
175/70R13	8.3	10.5	82	T	5	170	6.7	572	22.5	470	1036	44
185/70R13	8.6	10.8	85	T	5.5	181	7.1	586	23.1	515	1135	44
155/65R14	6.8	8.6	75	T	4.5	157	6.2	558	22.0	387	853	44
165/60R14	6.8	8.6	75	T	5	170	6.7	554	21.8	387	853	44
165/65R14	7.3	9.2	79	T	5	170	6.7	570	22.4	473	963	44
165/70R14	7.3	9.2	81	T	5	170	6.7	588	23.1	462	1019	44
175/65R14	8	10.1	81	T	5	173	6.8	583	22.9	462	1019	44
175/70R14	8.4	10.6	84	T	5	169	6.7	600	23.6	500	1102	44
185/55R14	8.4	10.6	80	H	6	194	7.6	560	22.0	450	992	44
185/60R14	8.4	10.6	82	T	5.5	189	7.4	576	22.7	475	1047	44
185/65R14	8.4	10.6	85	T	5.5	185	7.3	595	23.4	510	1124	44
185/70R14	8.6	10.8	87	T	5.5	181	7.1	611	24.1	545	1201	44
195/60R14	8.4	10.6	85	T	6	201	7.9	588	23.1	515	1135	44
195/70R14	8.6	10.8	90	T	6	193	7.6	628	24.7	595	1312	44
205/60R14	8.6	10.8	88	H	6	209	8.2	602	23.7	560	1235	44
205/70R14	8.4	10.6	98	T	6	209	8.2	644	25.4	750	1653	44
215/70R14	8.8	11.1	96	T	6.5	212	8.4	654	25.7	705	1554	44
175/55R15	7.3	9.2	77	T	5.5	182	7.2	573	22.6	412	908	44
175/60R15	7.3	9.2	81	H	5	177	7	591	23.3	462	1019	44
175/65R15	7.3	9.2	84	T	5	177	7	609	24.0	500	1102	44
185/55R15	7.3	9.2	82	V	6	184	7.2	585	23.0	475	1047	44
185/60R15	8.4	10.6	84	T	5.5	185	7.3	601	23.7	500	1102	44
185/65R15	8.4	10.6	86	T	5.5	181	7.1	617	24.3	530	1168	44
195/60R15	8.4	10.6	87	T	6	201	7.9	613	24.1	540	1190	44
195/65R15	8.4	10.6	89	T	6	197	7.8	633	24.9	580	1279	44
205/60R15	8.4	10.6	91	H	6	201	7.9	615	24.2	615	1356	44
205/65R15	8.8	10.6	92	T	6	206	8.1	645	25.4	635	1400	44
205/70R15	8.8	10.6	96	T	6	209	8.2	669	26.3	710	1565	44
215/60R15	7.3	9.2	94	V	6.5	221	8.7	639	25.2	670	1477	44
215/65R15	8.8	11.1	95	T	6.5	219	8.6	659	25.9	685	1510	44
215/70R15	8.8	11.1	97	T	6.5	212	8.4	679	26.7	735	1620	44
P225/70R15	9	11.3	100	T	6.5	219	8.6	693	27.3	795	1753	44
P235/70R15	9	11.3	102	S	7	240	9.4	711	28.0	860	1896	44
205/55R16	8.3	10.5	89	S	6.5	212	8.3	633	24.9	580	1279	44
215/60R16	8.8	11.1	94	T	6.5	219	8.6	662	26.1	670	1477	44
215/65R16	8.8	11.1	96	T	6.5	217	8.5	684	26.9	710	1565	44
225/60R16	9	11.3	97	T	6.5	226	8.9	674	26.6	730	7609	44
235/60R16	9	11.3	99	T	7	263	9.3	686	27.0	775	1709	44

