

A PLUS

ALL TERRAIN

A929

1. Four main zigzag grooves and rough lateral blocks provide excellent traction on all kinds of road conditions.
2. The open shoulder grooves prevent aquaplaning with enhanced wet grip performance and provide excellent water evacuation. The white letter styling provide a artistic image.
3. The block tread design with multiple-sipes provide outstanding off-road traction and reduce tread damage on off-road condition.



Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Max.Per miss Press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	bar	psi
P215/75R15	8.8	11.1	100	S	6J	216	8.5	703	27.7	800	1764	3	44
P235/75R15	8.8	11.1	105	S	6 1/2 J	235	9.3	733	28.9	925	2039	3	44
P215/70R16	8.8	11.1	99	T	6 1/2 J	221	8.7	708	27.9	775	1709	3	44
P225/70R16	8.8	11.1	102	T	6 1/2 J	228	9	722	28.4	850	1874	3	44
P235/70R16	8.8	11.1	104	S	7J	240	9.4	736	29	900	1984	3	44
P245/70R16	10.7	11.1	106	S	7J	248	9.8	750	29.5	950	2094	3	44
P255/70R16	8.8	11.1	109	S	7 1/2 J	260	10.2	764	30.1	1030	2271	3	44
P265/70R16	8.8	11.1	112	S	8J	272	10.7	778	30.6	1120	2470	3	44
P275/70R16	8.8	11.1	114	T	8J	271	10.7	790	31.1	1180	2601	3	44
P225/65R17	9.7	12.2	102	H	6 1/2 J	228	9	724	28.5	850	1874	3.5	51
P235/65R17	9.7	12.2	104	H	7J	240	9.4	738	29.1	900	1984	3.5	51
P245/65R17	8.8	11.1	105	T	7J	248	9.8	750	29.5	925	2039	3	44
P245/70R17	9.8	12.3	108	S	7J	245	9.6	776	30.6	1000	2205	3	44
P255/65R17	10.7	13.5	108	S	7 1/2 J	260	10.2	764	30.1	1000	2205	3	44
P265/65R17	9.7	12.2	112	H	8J	272	10.7	776	30.6	1120	2469	3.5	51
P265/70R17	9.7	12.2	113	H	8J	272	10.7	804	31.7	1150	2535	3.5	51
P275/65R17	9.7	12.2	113	H	8J	279	11	790	31.1	1150	2535	3.5	51
P275/65R18	11	13.6	114	S	8J	276	10.9	813	32	1180	2601	3	44
LT235/75R15	12.7	16	104	S	6.5	235	9.3	733	28.9	900	1985	3	44
			101							825	1820	3	44
LT31X10.5R15	12.7	16	109	S	6J	268	10.6	775	30.5	1030	2270	3	44
LT215/85R16	12.2	15.4	115	Q	6J	216	8.5	772	30.4	1215	2680	5.5	80
			112							1120	2470		
LT225/75R16	12.2	15.4	115	Q	6J	223	8.8	744	29.3	1215	2680	5.5	80
			112							1120	2470		
LT235/85R16	12.7	16	120	Q	6 1/2 J	235	9.3	806	31.7	1380	3042	5.5	80
			116							1260	2778		
LT245/75R16	10.7	13.5	120	S	7J	248	9.8	774	30.5	1380	3042	3	44
			116							1260	2778		
LT265/75R16	10.7	13.5	114	S	7 1/2 J	267	10.5	804	31.7	1180	2601	3	44
LT285/75R16	13.7	17.3	112	Q	8J	288	11.3	830	32.7	1500	3305	4.5	65
			119							1360	3000		
LT265/70R17	10.7	13.5	113	S	8J	272	11	804	31.7	1150	2535	3	44
215R15C	11.2	14.1	105	S	6J	218	8.6	724	28.5	925	2039	3	44

Remark: White Letter Styling