

A PLUS

A867

1. Three main zigzag grooves combined with lateral blocks provide excellent ride stability and great traction on all kinds of road conditions.
2. Continuous tread patterns on shoulder and solid shoulder ribs provide responsive handling and even wear.
3. Variable pitch patterns and multi-knife-cut tread pattern reduce vibration to offer the comfort and quiet ride.



Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Max.Per miss Press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	bar	psi
175/65R14C	8.8	11.1	90	T	5J	117	7	584	23.0	600	1323	3.75	54
			88									560	1235
165/70R14C	8.8	11.1	89	R	5J	170	6.7	588	23.1	580	1279		
			87									545	1202
185R14C	8.8	11.1	99	Q	6J	188	7.4	650	25.6	775	1709	3.75	54
			97									730	1609
195R14C	8.8	11.1	106	R	8J	198	7.8	666	26.2	950	2094	3.75	54
			104									900	1984
195R15C	8.8	11.1	106	R	5 1/2 J	198	7.8	690	27.2	950	2094	3.75	54
			104									900	1984
195/70R15C	8.8	11.1	104	R	6J	201	7.9	655	25.8	900	1984	3.75	54
			102									850	1874
205/70R15C	8.8	11.1	104	S	6J	209	8.2	669	26.3	875	1930	3.75	54
			102									825	1820
215/70R15C	8.8	11.1	109	S		221	8.7	683	26.9	1030	2271	3.75	54
			107									975	2150
225/70R15C	8.8	11.1	112	R	6 1/2 J	228	9.0	697	27.4	1120	2469		
			110									1060	2337
185/75R16C	8.8	11.1	104	T	5 1/2 J	196	7.7	698	27.5	1060	2337	3.75	54
			102									1000	2205
195/60R16C	8.8	11.1	99	T	6J	201	7.9	640	25.2	775	1709	3.75	54
			97									730	1609
195/65R16C	8.8	11.1	104	R	6J	201	7.9	660	26.0	900	1984	3.75	54
			102									850	1874
195/75R16C	8.8	11.1	107	R	5 1/2 J	196	7.7	698	27.5	975	2149	3.75	54
			105									925	2039
205/65R16C	8.8	11.1	107	T	6J	209	8.2	672	26.5	975	2149	3.75	54
			105									925	2039
205/75R16C	8.8	11.1	110	R	5 1/2 J	203	8.0	714	28.1	1060	2337	3.75	54
			108									1000	2205
215/60R16C	8.8	11.1	103	T	6 1/2 J	221	8.7	664	26.1	875	1930	3.75	54
			101									825	1820
215/65R16C	8.8	11.1	109	R	6 1/2 J	221	8.7	661	26.0	1030	2271	3.75	54
			107									975	2150
215/75R16C	8.8	11.1	116	Q	6J	215	8.5	728	28.7	1250	2756	3.75	54
			114									1180	2601
225/65R16C	8.8	11.1	109	T	6 1/2 J	225	8.9	698	27.5	1030	2271	3.75	54
			107									975	2149
235/65R16C	8.8	11.1	115	R	7J	240	9.4	712	28.0	1215	2679	3.75	54
			113									1150	2535
155R12C	8.8	11.1	83	P	4 1/2 J	127	6.2	550	21.7	487	1074	3.75	54
			81									462	1019
155R13C	8.8	11.1	90	R	4 1/2 J	144	5.7	564	22.2	560	1235	3.75	54
			88									530	1168

A PLUS

A867



Tire Size	Tread Depth		Load Index	Speed symbol	Std. Rim	Section Width		Overall Diameter		Load Capacity		Max. Per miss Press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	bar	psi
235/65R16C	8.8	11.1	112	S	7J	240	9.4	712	28.8	1120	2469	3.75	54
			110							1060	2337		