

FARALONG

FL 662



- ➔ Low rolling resistance for reduced fuel consumption.
- ➔ Lateral grooves on ribs for better traction. Longitudinal grooves on shoulder for even wear.

Suitable for

- ➔ Trailer position of truck.
- ➔ Highways, national roads, harbors and ports.



Tyre size	P.R	Standard rim	Overall Diameter mm	Section Width mm	Tread depth	Load		Pressere	
						S	D	S	D
10.00R20	16	7.5	1054	278	15	3000	2725	120	120
10.00R20	18	7.5	1054	278	15	3250	3000	135	135
11R22.5	14	8.2	1054	279	15	3800	2650	105	105
11R22.5	16	8.2	1054	279	15	3150	2900	120	120
11R24.5	14	8.2	1104	279	15	3000	2725	105	105
11R24.5	16	8.2	1104	279	15	3250	3000	120	120
255/70R22.5	14	7.5	930	255	14	2360	2120	760	760
395/75R22.5	14	9.0	1014	298	15	2800	2575	110	110
285/75R24.5	14	8.2	1050	283	15	2800	2575	110	110
12R22.5	16	9.0	1085	300	15	3550	3075	120	120
315/70R22.5	18	9.0	1016	308	15	3550	3150	125	125
295/80R22.5	18	9.0	1044	298	15	3550	3150	125	125
315/80R22.5	18	9.0	1076	312	15	3750	3450	120	120
245/70R19.5	18	7.5	848	393	14	2725	2575	110	110
245/70R19.5	16	7.5	797	372	13	2725	2575	110	110
235/75R17.5	16	6.8	801	374	13	2725	2575	110	110
235/75R17.5	18	6.8	801	374	13	2725	2575	110	110
225/70R19.5	14	6.8	811	226	12	1800	1700	110	110
215/75R17.5	16	6.0	775	363	12	2180	2060	110	110

FL 662